











PRODUCT OVERVIEW SOLARWATT SOLAR MODULES FOR UK AND NORDICS

	SOLARWATT Panel vision AM 3.0 black	SOLARWATT Panel vision AM 3.0 pure	SOLARWATT Panel vision AM 4.0 black	SOLARWATT Panel vision AM 4.0 pure	Vision 60M style (black edition)	Vision 60M style (slim edition)
						
Dimensions (mm)	1,755 ^{±2} x 1,038 ^{±2}	1,755 ^{±2} x 1,038 ^{±2}	1,722 ^{±2} x 1,134 ^{±2}	1,722 ^{±2} x 1,134 ^{±2}	1,700 ^{±2} x 1,000 ^{±2}	1,700 ^{±2} x 1,000 ^{±2}
Cells	120 PERC cells, bifacial	120 PERC cells, bifacial	108 PERC cells, bifacial	108 PERC cells, bifacial	60 PERC cells	60 PERC cells
Cell dimensions	166 x 83 mm	166 x 83 mm	182 x 91 mm	182 x 91 mm	159 x 159 mm	159 x 159 mm
Weight	24.0 kg	24.0 kg	25.4 kg	25.4 kg	22.0 kg	22.0 kg
Glass-glass 2x2mm	x	x	x	x	x	x
Glass-glass 2x4 mm						
Glass-foil						
White cell background		x		x		x
Black cell background	x		x			
Transparent cell background					x	
Frame thickness (mm)	35 ^{±0.3}	35 ^{±0.3}	35 ^{±0.3}	35 ^{±0.3}	35 ^{±0.3}	35 ^{±0.3}
Silver frame		x		x		x
Black frame	x		x		x	
Module = frame system						
Cable length	2x 1,2 m/4 mm ²	2x 1,2 m/4 mm ²	2x 1,2 m/4 mm ²	2x 1,2 m/4 mm ²	2x 1,0 m/4 mm ²	2x 1,0 m/4 mm ²
Stäubli Electrical connection, MC4	x*	x*	x*	x*	x	x
MC4-type						
Hirschmann connection, HC4						
TE Connectivity connection, PV4-S						
Performance classes	365 Wp	375 Wp	395 Wp, 400 Wp	405 Wp	325 Wp	330 Wp

* due to availability limitations of Stäubli MC4 connectors, we deliver module batches with MC4 type connectors from another supplier; align with order management to be sure which batch you are delivered with

PRODUCT OVERVIEW SOLARWATT SOLAR MODULES FOR UK AND NORDICS

	SOLARWATT Panel classic 2.0 black	SOLARWATT Panel classic 2.0 pure	SOLARWATT Panel classic 1.2 style	SOLARWATT Panel classic 1.1 pure
				
Dimensions (mm)	1,708 ^{±2} x 1,134 ^{±2}	1,708 ^{±2} x 1,134 ^{±2}	1,755 ^{±2} x 1,038 ^{±2}	1,755 ^{±2} x 1,038 ^{±2}
Cells	108 PERC cells	108 PERC cells	120 PERC cells	120 PERC cells
Cell dimensions	182 x 91 mm	182 x 91 mm	166 x 83 mm	166 x 83 mm
Weight	20.0 kg	20.0 kg	21.3 kg	21.3 kg
Glass-glass 2x2mm				
Glass-glass 2x4 mm				
Glass-foil	x	x	x	x
White cell background		x		x
Black cell background	x		x	
Transparent cell background				
Frame thickness (mm)	30 ^{±0,3}	30 ^{±0,3}	40 ^{±0,3}	40 ^{±0,3}
Silver frame		x		x
Black frame	x		x	
Module = frame system				
Cable length	2x 1,2 m/4 mm ²	2x 1,2 m/4 mm ²	2x 1,2 m/4 mm ²	2x 1,2 m/4 mm ²
Stäubli Electrical connection, MC4	x*	x*	x*	x*
MC4-type				
Hirschmann connection, HC4				
TE Connectivity connection, PV4-S				
Performance classes	400 Wp	405 Wp	370 Wp	375 Wp, 380 Wp

* due to availability limitations of Stäubli MC4 connectors, we deliver module batches with MC4 type connectors from another supplier; align with order management to be sure which batch you are delivered with